Cricut™

Cutting Vinyl with the Cricut® Machine

Step 1. Place vinyl sheet (liner side down) onto Cricut® cutting mat.

Step 2. Select images and size and load mat into the machine.

Step 3. Refer to Vinyl Kiss Cut Guide table to adjust machine settings. A kiss cut is a cut that only goes through the vinyl and leaves the liner intact.*

Step 4. Press CUT.

Preparation with Cricut® Transfer Tape

Step 1. Remove the negative pieces from each of the images using the Weeder found in the Cricut® Tool Kit, leaving the liner intact. This process is known as weeding.

Step 2. Remove the transfer tape liner.

Step 3. Gently place the transfer tape (adhesive side down) over the images. Use a craft stick or Scraper found in the Cricut® Tool Kit to burnish (rub or polish) the tape onto the vinyl. To prevent bubbles, start in the center and move out toward the edges.

Step 4. Peel away the vinyl liner at a 45-degree angle. If the vinyl sticks to the liner, simply burnish the transfer tape onto the vinyl and peel away again.

Application

Step 1. Make sure your project surface is clean and dry. Carefully place the transfer tape with vinyl images onto your surface how you would like them to appear.

Step 2. Burnish transfer tape onto the surface, starting in the center and moving out toward the edges. Use a craft stick or Scraper from the Cricut® Tool Kit.

Step 3. Peel away the transfer tape from the vinyl at a 45-degree angle. If the vinyl images stick to the transfer tape, simply burnish the transfer tape onto the surface again and then peel away transfer tape.

If you choose to cut through both the vinyl and the liner, you can peel the liner away from the vinyl and apply the vinyl to the surface by hand.

Cricut™

Cutting Vinyl with the Cricut® Machine

Machine	Blade Depth	Pressure	Speed	Multi-cut	Blade Assembly
Cricut Expression®	2	Medium	Medium	1	Regular
Cricut Expression® 2	3	3	Medium	1	Regular
Cricut Imagine®	3	2	Medium	1	Regular
Cricut Mini®	3	2	Medium	1	Regular
Cricut® / Cricut Create™	2	Low	Medium	1	Regular

Machines may vary. Always do a test cut to verify settings.